

Dimensions			
Notes		Specified value	Measured value
	Wheelbase	mm 2470	
	Track - front/rear	mm 1465/1450	
Tightening torques			
Notes		Specified value	Measured value
	Tightening torque - steel wheels	120-140 Nm	
	Tightening torque - alloy wheels	120-140 Nm	
	Trackrod locknut/clamp	50-55 Nm	
Checking range - Front wheels			
Notes		Specified value	Measured value
	Load positioning	Unladen	
	Toe-in (N = negative, toe-out)	mm 1,50N - 1,50P	
	Toe-in	deg 0°10'N - 0°10'P	
	Toe-in	deg-1/100 0,17N - 0,17P	
	Camber	deg 0°25'N - 0°35'P	
	Camber	deg-1/100 0,42N - 0,58P	
	Castor	deg 1°54' - 2°54'	
	Castor	deg-1/100 1,90 - 2,90	
Setting data - Four wheels			
Notes		Specified value	Measured value
	Load positioning	Unladen	
	Toe-in (N = negative, toe-out)	mm 0±1,50	
	Toe-in	deg 0°±10'	
	Toe-in	deg-1/100 0±0,17	
	Camber	deg 0°5'±30'	
	Camber	deg-1/100 0,08±0,50	
	Camber adjustment	Not adjustable	
	Castor	deg 2°24'±30'	
	Castor	deg-1/100 2,40±0,50	
	Castor adjustment	Not adjustable	
	Rear toe-in	mm 0±1,50	
	Rear toe-in	deg 0°±10'	
	Rear toe-in	deg-1/100 0±0,17	
	Rear toe-in adjustment	Not adjustable	
	Rear camber	deg 0°45'N±30'	
	Rear camber	deg-1/100 0,75N±0,50	
	Rear camber adjustment	Not adjustable	

**Manufacturer:** Mitsubishi  
**Engine code:** 4G63  
**Tuned for:** R-Cat

**Model:** Eclipse 2,0 Turbo  
**Output:** 147 (200) 6000  
**Year:** 1991-95

© Autodata Limited 2006  
 07.02.2006  
 V6.200- ***/Autodata***